



SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/11/2022 Revision date: 3/29/2023 Supersedes: 5/17/2017 Version: 2.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SafeGard Low Ash SAE 15W-40 NG Engine Oil
Product code : 592202

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Natural Gas Engine Oil

1.3. Supplier

Martin Lubricants
484 East 6th St.
Smackover, AR 71762

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labelling

No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Lubricating oils, petroleum, hydrotreated spent	CAS-No.: 64742-58-1	35 – 70
White Mineral Oil	CAS-No.: 8042-47-5	10 – 20
Distillates, hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	10 – 20
Zinc salts of dialkyl dithiophosphoric acid	CAS-No.: 68649-42-3	0.1 – 1.0

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%
Phenol, (tetrapropenyl) derivatives	CAS-No.: 74499-35-7	0.01 – 0.05
Calcium Branched Alkylphenol	CAS-No.: 132752-19-3	0.01 – 0.05
Distillates (petroleum), hydrotreated middle	CAS-No.: 64742-46-7	0.012 – 0.02

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SafeGard Low Ash SAE 15W-40 NG Engine Oil

No additional information available

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

No additional information available

White Mineral Oil (8042-47-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	5 mg/m ³
---------------	---------------------

Distillates, hydrotreated heavy paraffinic (64742-54-7)

No additional information available

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)

No additional information available

Phenol, (tetrapropenyl) derivatives (74499-35-7)

No additional information available

Calcium Branched Alkylphenol (132752-19-3)

No additional information available

Distillates (petroleum), hydrotreated middle (64742-46-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Amber, clear liquid.
Colour	: Amber
Odour	: Mild petroleum; Hydrocarbon
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 260 °C
Flash point	: 236 °C (456.80°F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: Negligible at STP
Relative vapour density at 20 °C	: 1
Relative density	: 0.87
Density	: 7.22 lb/gal
Solubility	: Material nearly insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 92.61 mm ² /s at 40°C (104°F), 14.44 cSt at 100°C (212°F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

White Mineral Oil (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5 mg/l
Distillates, hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)	
LD50 oral rat	3195 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5000 mg/m ³ Source: ECHA
ATE US (oral)	3195 mg/kg bodyweight
Distillates (petroleum), hydrotreated middle (64742-46-7)	
LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rabbit	> 2000 mg/kg Source: EHCA
LC50 Inhalation - Rat (Dust/Mist)	> 4.6 mg/l Source: ECHA
ATE US (dust,mist)	1.5 mg/l/4h

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation : Not classified

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)	
pH	5.5 – 7.5 Source: ECHA

Serious eye damage/irritation : Not classified

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)	
pH	5.5 – 7.5 Source: ECHA

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : 92.61 mm²/s at 40°C (104°F), 14.44 cSt at 100°C (212°F)

White Mineral Oil (8042-47-5)	
Viscosity, kinematic	> 3 mm ² /s

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)	
Viscosity, kinematic	9 – 15 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:'

Distillates (petroleum), hydrotreated middle (64742-46-7)	
Viscosity, kinematic	> 20.5 mm ² /s (40 °C, Niet experimenteel bepaald; afgeleid van de indeling)
Hydrocarbon	Yes

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

White Mineral Oil (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l

Distillates, hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)	
LC50 - Fish [1]	1 – 5 mg/l Source: ECHA
EC50 - Crustacea [1]	1 – 1.5 mg/l Source: IUCLID
EC50 96h - Algae [1]	1 – 5 mg/l Source: IUCLID

Phenol, (tetrapropenyl) derivatives (74499-35-7)	
LC50 - Fish [1]	0.146 mg/l Source: ECOSAR
EC50 96h - Algae [1]	0.6 mg/l Source: ECOSAR

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

White Mineral Oil (8042-47-5)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

White Mineral Oil (8042-47-5)

BCF - Other aquatic organisms [1]	1216 l/kg
Partition coefficient n-octanol/water (Log Pow)	5.18
Bioaccumulative potential	Potential for bioaccumulation ($500 \leq \text{BCF} \leq 5000$).

Distillates, hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)

Partition coefficient n-octanol/water (Log Pow)	14.876 Source: ECHA
---	---------------------

Distillates (petroleum), hydrotreated middle (64742-46-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

12.4. Mobility in soil

White Mineral Oil (8042-47-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.64
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	Present	Active	
White Mineral Oil	8042-47-5	Present	Active	
Distillates, hydrotreated heavy paraffinic	64742-54-7	Present	Active	
Zinc salts of dialkyl dithiophosphoric acid	68649-42-3	Present	Active	
Phenol, (tetrapropenyl) derivatives	74499-35-7	Present	Active	
Calcium Branched Alkylphenol	132752-19-3	Present	Active	
Distillates (petroleum), hydrotreated middle	64742-46-7	Present	Active	

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the Canadian DSL (Domestic Substances List)

White Mineral Oil (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

Distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)

Listed on the Canadian DSL (Domestic Substances List)

Phenol, (tetrapropenyl) derivatives (74499-35-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Calcium Branched Alkylphenol (132752-19-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Distillates (petroleum), hydrotreated middle (64742-46-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

White Mineral Oil (8042-47-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Zinc salts of dialkyl dithiophosphoric acid (68649-42-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), hydrotreated middle (64742-46-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SafeGard Low Ash SAE 15W-40 NG Engine Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations


California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/29/2023

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Martin Operating Partnership L.P.'s knowledge; however, Martin Operating Partnership L.P. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Martin Operating Partnership L.P. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Martin Operating Partnership L.P., must rely upon information provided by the material manufacturers or distributors.