

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 11/14/2022 Revision date: 1/11/2023 Supersedes: 5/4/2017 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name TurbineGard R&O ISO 22

Product code 573933

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricating oil

1.3. Supplier

Martin Lubricants 484 East 6th St. Smackover, AR 71762

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Carcinogenicity, Category 1B H350 May cause cancer. Hazardous to the aquatic environment - Acute Hazard, Category 3 H402 Harmful to aquatic life

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US) Danger

Hazard statements (GHS US) H350 - May cause cancer. H402 - Harmful to aquatic life

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Lubricating oils, petroleum, hydrotreated spent	CAS-No.: 64742-58-1	≥ 70
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0	10 – 20
Distillates, hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	0.15 – 0.21

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

1/11/2023 (Revision date) US - en 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle

until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers.

Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors,

walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke

when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TurbineGard R&O ISO 22

No additional information available

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

No additional information available

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

No additional information available

Distillates, hydrotreated heavy paraffinic (64742-54-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

1/11/2023 (Revision date) US - en 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Amber, clear liquid.

Colour : Amber

Odour : Mild petroleum; Hydrocarbon

Odour threshold : No data available : No data available рΗ Melting point : Not applicable No data available Freezing point

Expected to be > 260°C (500°F) Boiling point

Flash point 214 °C (417.20°F) Relative evaporation rate (butylacetate=1) : Negligible at STP

Flammability (solid, gas) : Flash Point at or above 200 °F

> Not applicable. : Negligible at STP

: 7.12 lb/gal

Vapour pressure Relative vapour density at 20 °C : > 1 at STP Relative density : 0.85 Density

Material nearly insoluble in water. Solubility

Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature No data available Decomposition temperature : No data available

: 22.09 mm²/s at 40°C (104°F); 4.43 cSt at 100°C (212°F) Viscosity, kinematic

Viscosity, dynamic : No data available : No data available **Explosive limits** Explosive properties : No data available Oxidising properties : No data available

9.2. Other information

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LD50 oral rat	> 5000 mg/kg Source: IUCLID	
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID	
LC50 Inhalation - Rat (Dust/Mist)	2.18 mg/l Source: IUCLID	
ATE US (dust,mist)	2.18 mg/l/4h	

Distillates, hydrotreated heavy paraffinic (64742-54-7)

	·
LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified : Not classified Respiratory or skin sensitisation Germ cell mutagenicity : Not classified Carcinogenicity : May cause cancer. : Not classified Reproductive toxicity STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
	(Repeated Dose 90-Day Oral Toxicity Study in Rodents)

1/11/2023 (Revision date) US - en 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)
--

NOAEL (dermal, rat/rabbit, 90 days) ≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose

Dermal Toxicity: 21/28-Day Study)

Aspiration hazard : Not classified

Viscosity, kinematic : 22.09 mm²/s at 40°C (104°F); 4.43 cSt at 100°C (212°F)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID	
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID	
Distillates, hydrotreated heavy paraffinic (64742-54-7)		
LC50 - Fish [1]	> 5000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID	

12.2. Persistence and degradability

EC50 96h - Algae [1]

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Persistence and degradability	Biodegradability in water: no data available.

> 1000 mg/l Source: IUCLID

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Partition coefficient n-octanol/water (Log Pow) 3.9 – 6		
Bioaccumulative potential No bioaccumulation data available.		
Distillates, hydrotreated heavy paraffinic (64742-54-7)		
Partition coefficient n-octanol/water (Log Pow) 3.9 – 6 Source: IUCLID		

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

1/11/2023 (Revision date) US - en 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	Present	Active	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Present	Active	
Distillates, hydrotreated heavy paraffinic	64742-54-7	Present	Active	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List)

Distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates, hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/11/2023

Full text of H-statements	
H350	May cause cancer.
H402	Harmful to aquatic life

Safety Data Sheet (SDS), USA

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Martin Operating Partnership L.P. sknowledge; however, Martin Operating Partnership L.P. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Martin Operating Partnership L.P. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Martin Operating Partnership L.P., must rely upon information provided by the material manufacturers or distributors.