



**PREMIUM AW
HYDRAULIC OIL**

6,000 Hour Oxidation Life
For High Pressure, High Temperature Applications



REV: 09.30.2020



DESCRIPTION

Gard™ Premium Anti-Wear ISO Hydraulic Oils are blended from premium Group II base oils. This product has outstanding resistance to high temperature oxidation, thermal stability, color, and the ability to stay in grade over long periods of time. The oils are blended using an advanced additive system for maximum resistance to oxidation and foaming and contain a high level of zinc based anti-wear additives.

BENEFITS

- ▣ Long service life in severe conditions
- ▣ Inhibit rust, corrosion, foaming, and aids in water tolerance
- ▣ Contains zinc anti-wear additives for maximum protection for gears and rotors
- ▣ Excellent low-temperature performance

APPLICATION

- Hydraulic systems operating under high pressure and high heat
- Farm tractors with separate add-on hydraulic tanks for buckets, bale spikes, etc.
- Construction equipment such as front-end loaders and excavators where AW oils are recommended
- Logging equipment such as skidders, feller bunchers, harvesters, and loaders where AW oils are recommended
- General commercial applications such as hydraulic lifts in muffler shops, scissor lifts, trash compactors
- Dump trucks, hydraulic jacks, log splitters, car haulers, lift gates, hydraulic presses, forklifts

PERFORMANCE

Performance Levels

- Cincinnati Milacron P-68 (ISO-32), P-69 (ISO-46), P-70 (ISO-68)
- Vickers I-286-S (Industrial), M-2950 (Mobile)
- Denison HF-0, HF-2 equivalent

TYPICAL PROPERTIES	METHOD	ISO 15	ISO 22	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
API Gravity	D-1298	34.3	33.2	32.0	30.9	29.9	28.4	30.4
Specific Gravity at 15.6°C	D-1298	0.853	0.859	0.865	0.871	0.877	0.885	0.874
Viscosity, cSt at 40°C	D-0445	16.3	23.1	32.5	46.7	67.0	99.8	147.2
Viscosity, cSt at 100°C	D-0445	3.8	4.5	5.5	6.8	8.5	11.2	14.2
Viscosity Index	D-2270	126	105	106	100	96	97	93
Flash Point, °C	D-0092	196	205	220	230	238	243	232
Pour Point, °C	D-0097	-38	-41	-38	-26	-20	-20	-18
Oxidation Life	D-0943	5000+	6000+	6000+	6000+	6000+	-	-
ML Reference No.		588801	588481	566899	566910	566881	573925	571532



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Gard™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners