



## DOT BRAKE FLUID

Automotive & Heavy-Duty DOT 3 Fluid  
High Boiling Point for Extended Life



REV: 07.17.2024



### DESCRIPTION

Gard™ DOT 3 Brake Fluid is a high boiling formulation designed for service fill or complete fill of all passenger cars, light trucks, SUV's and heavy-duty equipment where DOT 3 fluids are required.

Gard DOT 3 Brake Fluid has a high boiling point for extended service life under adverse conditions.

Gard DOT 3 Brake Fluid is suitable for use with conventional drum or disc brake systems. This fluid is compatible with all DOT 3 and DOT 4 fluids.

### BENEFITS

- ❑ Low moisture activity reduces corrosion and extends service life
- ❑ Compatible with all seals and metals found in braking systems
- ❑ Compatible with all DOT 3 and DOT 4 fluids
- ❑ Excellent service fill or complete fill fluid

### APPLICATION

For all passenger cars, light trucks, SUVs, or heavy-duty equipment where DOT 3 fluids are recommended.

### PERFORMANCE RATING

- DOT: Type 3 Motor Vehicle Brake Fluid
- U.S. Government: Federal Motor Vehicle Safety Standard
- 116 • SAE: J1703
- ISO: 4925

TYPICAL PROPERTIES	METHOD	Range	Brake Fluid DOT 3
Specific Gravity at 15.6°C	D-1298	1.03-1.06	1.05
Viscosity, cSt at 40°C	D-445	Report	7.63
Viscosity, cSt at 100°C	D-445	1.5 min	1.96
Viscosity, cP at -40°C	D-2983	1500 max	1235
Flash Point, COC °C	D-92	118 min	133
Original ERBP °C		243 min	257
Wet ERBP °C		140 min	151



#### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Gard™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners