

HEAT TRANSFER OIL

Outstanding Resistance to Oxidation

Ideal for Use in Asphalt and Chemical Heating Systems



REV:



DESCRIPTION

Gard™ Heat Transfer Oils are designed for use in industrial heating systems where fuel oil, used motor oil, gas, or electricity is used to heat a fluid and the fluid then transfers heat to the designated material. Typical applications would include heating of asphalt and process chemicals for use in industrial applications and chemical plants.

Gard Heat Transfer Oil is made with premium quality highly refined petroleum base stocks and special thermal stability additives and is blended for long service life with high resistance to oxidation. This product has excellent low temperature properties for outdoor use in cold weather.

BENEFITS

- High thermal stability
- Strong oxidation inhibitors
- Resists oil thickening
- Excellent heat transfer characteristics
- Outstanding high temperature service life

APPLICATION

- Asphalt and chemical heating systems
- Service life depends on the maximum operating temperature, the metallurgy of the circulating system, and contaminants that build up in the oil

TYPICAL PROPERTIES	METHOD	ISO 22	ISO 32	ISO 46	ISO 68	ISO 100
Color, ASTM	D-1500	L 1.0				
API Gravity	D-4052	34.3	32.9	31.8	31.9	31.6
Viscosity, cSt at 40°C	D-445	22.0	32.5	46.1	67.3	99.8
Viscosity, cSt at 100°C	D-445	4.4	5.6	7.0	9.3	12.3
Viscosity Index	D-2270	109	108	107	116	115
Flash Point, COC °C	D-92	213	225	239	261	282
Flash Point, °F	D-92	415	437	462	501	540
Pour Point, °C	D-97	-47	-45	-40	-37	-38
Pour Point, °F	D-97	-53	-49	-40	-35	-36
ML Reference No.		593264	574071	574080	574101	588730



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Gard™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners

